



Advantages of Conferencing With Emblaze-VCON VCBPro

- ↘ Video Transcoding for H.261, H.263 and H.264 in 720p, 4CIF and CIF resolutions in Voice Switching and Continuous Presence.
- ↘ AAC-LD audio support with transcoding.
- ↘ Recording and streaming capabilities
- ↘ Up to 36 participants at any number of conferences with max. bandwidth of 4Mbps.
- ↘ Continuous Presence allows users to see up to 25 participants on screen.
- ↘ Password Protected Conferences.
- ↘ Multilingual Voice Notifications.
- ↘ MS Outlook integration for fast and easy scheduling.
- ↘ VCBPro Cluster Mode to ensure continuous operation.
- ↘ Allows mixed H.323 and SIP endpoints in a single multipoint conference and ISDN thru external Gateway.
- ↘ Supports Emblaze-VCON's Broadcast Viewer for viewing VCBPro recorded and streamed sessions.
- ↘ Special Backup & Recovery engine.



All-In-One, High Definition MCU with Unique Cascading, Video Recording and Streaming Capabilities

The VCBPro is Emblaze-VCON's all-in-one, high definition MCU that integrates multipoint conferencing, advanced video management capabilities, video recording, streaming and scheduling in a single, cost-effective appliance. An advanced yet easy-to-use solution that optimizes your enterprise's videoconferencing network, the VCBPro includes an embedded MXM, Emblaze-VCON's full-feature management tool. It also comprises features such as Continuous Presence intelligent conference layouts for up to 25 participants at a time, and a special Presenter Mode for remote education and other vertical markets. Users can invite any number of participants to an ad-hoc or prescheduled conference at any bandwidth, and video resolution. The VCBPro includes all the latest audio, video and data algorithms, ensuring that calls involving standards-based videoconferencing endpoints connect and operate smoothly. The VCBPro is scalable from 6 to 36 ports and now offers a unique and configurable cascading capability across multiple VCBs for larger conferences.

Advanced Management System and Gatekeeper

The VCBPro includes an embedded MXM, Emblaze-VCON's award winning, full-feature management tool, for exceptional video network management and total gateway functionality for legacy and advanced technologies. From a single console in the office, home or on the road, it provides the ability to configure, monitor, manage, upgrade and enforce company conferencing policies on any videoconferencing client in the organization. The MXM also offers a full suite of tools for centrally managing and administering bandwidth requirements as well as QoS prioritization for each endpoint, a billing engine and reporting capabilities. Full video telephony features include: follow-me, forward when busy, no answer, pick-up, easy dialing to systems outside the organization and directory listing.

WMV Recording and Streaming

Now offering high definition, WMV session recording, the VCBPro enables every videoconference session to be recorded, stored and forwarded, allowing even absent colleagues to remain fully updated instantaneously and providing definitive session records. The VCBPro also contains the unique WMV streaming feature that allows live streaming of point-to-point or multipoint conferences while hundreds or thousands of other users can watch the stream through a simple viewer application.

Using Emblaze-VCON's free-of-charge Broadcast Viewer, anyone on the network can see what sessions are being broadcast and can view the appropriate one.

Web-based Manager and Moderator

The VCBPro Manager offers full-featured, web-based applications for scheduling, status monitoring, configuration and conference moderation capabilities. During conferences, managers have chair control options, and can change display layouts. Additional conference moderation capabilities include adding / removing participants, and starting / stopping multicast streaming of the conference. Administrators can also set up call services which are used to connect multipoint calls. The Manager interface is intuitive, user-friendly and can be viewed in several different languages.



Video Made Easy

Specifications

**Emblaze-VCON, Inc.,
Americas**
2 University Plaza, Suite 201
Hackensack, NJ 07601
USA
Tel: +1-201-883-1220
Fax: +1-201-883-1229

**Emblaze-VCON
China**
Unit 1321, Tower B, COFCO Plaza
8 Jianguomennei Avenue
Beijing, 10005
China
Tel: +86-10-6526-9791
Fax: +86-10-6526-9790

**Emblaze-VCON
CE, NE, WE and Russia**
MMG Multimedia GmbH
Akazienstr. 1
16356 Wemeuchen
Germany
Tel: +49-333-98-78530
Fax: +49-333-98-78539

**Emblaze-VCON
Italy**
Satnet s.r.l
Via Abegg, 43
10050 Borgone Susa (TO)
Italy
Tel: +39-01-196-41375
Fax: +39-01-197-62802

**Emblaze-VCON
Eastern Europe**
Ramiris Communications Ltd
Frangepan, u.46
H-1139 Budapest
Hungary
Tel: +36-1-889-7607
Fax: +36-1-889-7601

**Emblaze-VCON
UK and Middle East**
27 Old Gloucester Street
London, WC1N 3XX
United Kingdom
Tel: +44 (0)207-0317-255
Fax: +44 (0)207-0316-256

**Emblaze-VCON Ltd.
Headquarters**
Beit Rakefet
1 Emblaze Square
POB 2220
Ra'anana 43662
Israel
Tel: +972-9-7627800
Fax: +972-9-7627801

VCBPro Models

Model Name	12	24	36
No. of user ports	12	24	36
Gatekeeper size	25-port	50-port	50-port
Web-based Management	Yes	Yes	Yes
Recording Capability	Yes	Yes	Yes
Streaming capability	Yes	Yes	Yes
Software subscription	Yes	Yes	Yes

Communications Standards
H.323, SIP, LDAP, HTML/HTTP, FTP,
SMTP, RTP/RTCP

ITU-T Standards
H.323, H.350, H.239, H.235

Audio Standards
20 KHz: AAC-LD
14 KHz: G.722.1 Annex C
7 KHz: G.722, G.722.1
8 KHz: G.729
3.4KHz: G.711, G.723.1, G.728
Audio transcoding

Video Standards
H.264, H.263+, H.263+, H.263,
H.261
Resolutions: CIF, 4CIF, 720p
H.239: VGA, SVGA, XGA
H.281 Annex Q (FECC)

Data Rate
30 fps up to 4 Mbps/participant
(H.263, H.264)
30 fps up to 1 Mbps/participant
(H.261)

Scalability and Performance
Up to 36 ports in CP or VS

**Web-based Management —
Moderator, Scheduler, VCBPro
Configuration**

User ID/password authentication
Add/remove participants
User roles and permissions
Group management
Time zone coordination
Services configuration
Chair control modes:
Lecture Mode
Fixed
Automatic Layout Transition
Dominant speaker
Scheduling calls
Microsoft Outlook Integration
Point-to-point
Multipoint
Recurring
E-mail notification
Start/Stop Recording
Start/Stop Streaming
Advanced Cascading

Session configuration:
VS or CP
Number of participants
Password Protected conference
Rich, intelligent layouts
Audio algorithm
Conference data rate
Start/stop multicast
Automatic Recording

Configuration
Licensed in 12-port increments
Cascading: VCB-VCB, VCB-other IP
MCU

Gatekeeper Compatibility
Emblaze-VCON MXM
Any standard H.323 gatekeeper

Security
H.235 (AES) encryption
Emblaze-VCON Frontier
Emblaze-VCON SecureConnect
DES, 3DES, AES

Quality of Service (QoS) Features
IP Precedence
DiffServ
RTP/RTCP port range configuration
H.245 port range configuration

High Availability Features
Hard Drive: RAID1 (mirroring)
Memory: Dual 1GB
NIC: Quad 10/100/1000 Mb Ethernet
Redundant Power Supply
Front LCD for IP Address retrieval,
Restart or Shutdown
Software Service Watchdog



EMBLAZE VCON

Video Made Easy

www.emblaze-vcon.com

customercare@emblaze-vcon.com

©2008 Emblaze-VCON. All rights reserved.
DOC50102 Rev. 13 04/08

